


### **TECHNICAL DATASHEET**

## BTA-70834-3

## Adapter, BB-2590/U Charge/Discharge

#### **Features**



- Can be used for an individual battery or combined in series or parallel for multi-battery applications.
- Compatible with the following types of batteries:
  - BB-2590/U (BT-70791A, BT-70791Bx, or BT-70791Cx)
  - BB-390B/U (BT-70790 or BT-70790B)
  - BB-2557/U (BT-70757 or BT-70757Bx)



#### **Related Products**

BTA-70762-x Series (SMBus Charge/Discharge Cable)

Technical Specifications	
National Stock Number	Pending
BT Part Number	BTA-70834-3
Dimensions	Length: 2.71 in (68.8 mm) Width: 1.92 in (48.77 mm) Height: 1.56 in (39.63 mm)
	Cable Length: 26.0 in (0.66 m)
Weight	0.30 lbs (0.14 kg)
Operating Temperature	-20°C to +50°C (-4°F to +122°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Material/Color	Plastic/Metal Connector/Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: http://www.bren-tronics.com



# HEADQUARTERS United States

10 Brayton Court, Commack, NY 11725 Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816

United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.