

Bren-Tronic, Inc. Intelligent Military Batteries & Charging Systems™

J-6581/U

TECHNICAL DATASHEET VMC Adapter for BB-390B/U or BB-2590/U

Batteries

Features

- Bulk adapter for charging on (1) to four (4) BB-390B/U or BB-2590/U batteries in any combination.
- The BTA-70820 when used in conjunction with the appropriate battery charger will charge the following batteries in the appropriate positions
 - Position 1-4: BB-2590/U (BT-70791A or BT-70791BK) in 3 hours or less*
 - Position 1-4: BB-390B/U (BT-70790) in 4 hours or less




*Additional higher capacity versions of the BB-2590/U are available and can be

charged in positions 1-4 with slightly longer charge times.

Related Products

- BTC-70836 (Vehicle Mounted Charger)
- BTC-70870 (Vehicle Mounted Charger Lite)
- BTC-70870-1 (Vehicle Mounted Charger Lite, 24VDC Only)
- BTC-70870-3 (Vehicle Mounted Charger Lite, 12VDC)

Technical Specificatio	ns		
National Stock Number		5940-01-494-7116	
BT Part Number		BTA-70820	
Dimensions		Length: 9.3 in (235 mm) Width: 5.9 in (150 mm) Height: 3.6 in (90 mm)	
Weight		1.3 Lbs (0.59 Kg)	
Operating Temperature		-20°C to +50°C (-4°F to +122°F)	
Storage Temperature		-40°C to +70°C (-40°F to +158°F)	
Material/Color		Modified ABS Plastic / Olive Drab	
Disposal		Environmentally Safe – Contains Zero (0)% Mercury or Cadmium	
For a complete description of our products refer to Bren-Tronics	United States	Europe	United Kingdom
website at: http://www.bren-tronics.com	10 Brayton Court Commack, NY 11725-3197 Phone: 1-631-499-5155 Fax: 1-631-499-5504	20 rue Henri Regnault 75014, Paris, France Phone: +33(0)1-40-59-8051 Fax: +33(0)1-45-41-5816	Brunel House, Volunteer Way Faringdon, Oxfordshire SN7 7YR United Kingdom Phone: +44-1367-246027 Fax: +44-1367-246041



高深東