

BTA-70782(R)

Solar Adapter BB-2590/U (RoHS)

Features

- The BTA-70782(R) solar adapter can charge one (1) BB-2590/U or BB-2557/U battery.
- The adapter's rugged design is well suited for outdoor use, and velcro strapping provides the adapter with additional security to the battery.
- This adapter when used in conjunction with the charge controller (BTC-70824-1) will charge one (1) of the following batteries:
BB-2590/U in 7 hours or less
BB-2557/U in 3 hours or less



(BTA-70782 SHOWN)

Related Products

BTC-70824-1 (CHARGER, Li ION, REPPS)



Technical Specifications

National Stock Number	Pending
BT Part Number	BTA-70782(R)
Dimensions	Length: 3.5 in (89 mm) Width: 2.0 in (51 mm) Height: 2.7 in (70 mm)
Weight	0.6 lbs (0.27 kg)
Operating Temperature	-20°C to +50°C (-4°F to +122°F)
Storage Temperature	-40°C to +70°C (-40°F to 158°F)
Material/Color	High Impact ABS/Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: <http://www.bren-tronics.com>



HEADQUARTERS United States

10 Brayton Court, Commack, NY 11725
Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816
 United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.