


TECHNICAL DATASHEET

BTA-70781A

Isolated BB-2590/U Pass Thru

Features



- When connected to the solar charger and power source provides up to 1.75A to each section of the battery while the battery provides power to the application.
- The output of this cable is 14.4V or 28.8V nominal depending on wiring.
- The BTA-70781A cable provides the same output and pin out as the BB-2590/U and BB-2557/U batteries.
- Multiple Isolated Pass Thru cables can be connected together via de daisy chain connector for increased capacity and power output.



Related Products

BTC-70663 (Advanced Solar Charge Controller)

BTA-70781 (BB-2590/U Pass Thru)

BTA-70781-1 (BB-2590/U Pass Thru for Jim LR Camera)

BTA-70781B (BB-2590/U Isolated Pass Thru for High Power Systems)

Technical Specifications	
National Stock Number	5325-01-609-0355
BT Part Number	BTA-70781A
Dimensions	Cable Length: 23.0 in (584 mm)
Weight	0.75 lbs (0.34 kg)
Operating Temperature	-20°C to +50°C (-4°F to +122°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Material/Color	ABS / Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: http://www.bren-tronics.com



HEADQUARTERS United States

10 Brayton Court, Commack, NY 11725 Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816

United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.