

TECHNICAL DATASHEET

BTC-70911-10

FLEX Charger®

FOLDABLE LIGHTWEIGHT EXPEDITIONARY CHARGER

2 Panel DUAL PRC148/152, SPR/BB-2590

Features

- Dedicated two (2) panel foldable compact charger for the Falcon Handheld (AN/PRC-152),
 MBITR (AN/PRC-148) BT-70716Bx, and BB-2590/U BT-70791Cx batteries.
- Will charge two (2) sets of two (2) batteries in 4.5-6 hours depending on the input power.
- Simultaneously charges like-batteries.
- Powered from 20-36Vdc, 120W (max), or a Solar Panel.
- Incorporates advanced features such as Maximum Power Point Tracking (MPPT) which allows the batteries to be charged more efficiently by constantly adjusting to utilize the maximum power available from a solar panel.
- Equipped with a 10W USB charging port.
- Equipped with a trailer hitch connector for connection with multiple existing input cables.
- Blackout button for stealth operation.
- Visit: www.bren-tronics.com/patents for patent information.
- CE Compliant



Related Products

BTC-70911-x (Multiple FLEX Charger® Variations)

BTA-70671 (24Vdc Nato Input)

BTA-70768 (X90 Scavenger)

BTA-70784 (DC Cable with Alligator Clips)

BTK-70887H1-x (Power Source Kit)

BTK-70887M1-x (Power Source Kit)

BTP-592400-x (Solar Panel, 60W)

BTP-592433-MC (Solar Panel, 60W)

BTP-592436-MC (Solar Panel, 120W)

Technical Specifications			
National Stock Number		Pending	
BT Part Number		BTC-70911-10	
Dimensions	Folded	Length: 5.0 in (127 mm) Width: 5.6 in (143 mm) Height: 3.0 in (76 mm)	
	Unfolded	Length: 13.5 in (343 mm) Width: 5.6 in (143 mm) Height: 1.8 in (44 mm)	
Weight		1.19 lbs (0.54 kg)	
Input Power		20-36Vdc	
Operating Temperature		-20°C to +50°C (-4°F to +122°F)	
Storage Temperature		-40°C to +70°C (-40°F to 158°F)	
Material/Color		Modified ABS Plastic/Tan on Green Camo Fabric Carrier	
Disposal		Check local regulations (Contains 0% Mercury or Cadmium)	
Prop Tranics is an advanced designer and manufacturer of primary		E T ULADOUADTEDO	

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: http://www.bren-tronics.com



HEADQUARTERS United States

10 Brayton Court, Commack, NY 11725 Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816

United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.