



TECHNICAL DATASHEET

BTA-70100-DC12-1

CABLE, ABC, 12VDC POWER, RING LUG



Features

- The BTA-70100-DC12-1 is a standard 12Vdc cable (with ring lug terminations), used for powering the Advanced Battery Charger (ABC).
- Integral identification feature prompts the ABC to automatically configure its under-voltage lockout (UVLO) and input-current limit to support operation within the limits below:
 - Input-voltage range: 11-36Vdc
 - Input current (max.): 46A
 - Input power (max.): 1000W

Related Products

BTC-70100 (Advanced Battery Charger)



Technical Specifications

National Stock Number	Pending
BT Part Number	BTA-70100-DC12-1
Dimensions	Cable Length: 96 in (2.4 m)
Weight	1.53 lbs (0.7 kg)
Operating Temperature	-20°C to +50°C (-4°F to +122°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Material/Color	Rubber with Metal Connector/Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: <http://www.bren-tronics.com>



HEADQUARTERS

United States

10 Brayton Court, Commack, NY 11725
Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816

United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.