

BB-287/U

Rechargeable, Nickel Cadmium Battery



Product Note:

Rechargeable, Nickel Cadmium Battery

Typically Used in:

TOW, Anti-Tank Guided Missile System

Charging Note:

Charge at constant current of 1 Amp for 5 to 6 Hours

When Ordering Specify P/N:

BT-70410

Technical Data

National Stock Number	6140-00-454-8261
BT Part No.	BT-70410
Dimensions	Length: 15.5 in (394 mm) Width: 4.8 in (122 mm) Height: 8.5 in (216 mm)
Weight	23.0 Lbs (10.4 Kg)
Voltage	Section 1 (24.0 V), Section 2 & 3 (50.4 V) each
Capacity	Section 1 (4.5 Ah), Section 2 & 3 (1.4 Ah) each
Operating Temperature	-20°C to +55°C (-4°F to +131°F)
Storage Temperature	-40°C to +40°C (-40°F to +104°F)
Connector	Per U.S. Missile Dwg. # 10084532
Disposal	Battery contains Cadmium. Check with local regulations for proper disposal

For a complete description of our products refer to Bren-Tronics website at: <http://www.bren-tronics.com>

10 Brayton Court, Commack, NY 11725 Tel 631.499.5155 Fax 631.499.5504
Email sales@bren-tronics.com www.bren-tronics.com