



TECHNICAL DATASHEET

BTA-70903

SPC Adapter BB-2590/U Batteries

Features

- This adapter is a two (2) position charge adapter for BB-2590/U batteries on SPC chargers
- The BTA-70903 adapter will charge the Bren-Tronics BB-2590/U batteries to 33.6V (in series mode) or 16.8V (in parallel)
- The BTA-70903 when used in conjunction with the appropriate battery charger will charge one (1) or two (2) of the following batteries:
 - BB-2590/U (BT-70791Bx, BT-70791Cx or BT-70791Jx)
 - BB-390/U (BT-70790B)

Note: Do not install batteries charged to 33.6V (in series mode) in equipment not rated for 33.6V operation

Related Products

BTC-70801 (Soldier Portable Charger) BTC-70844 (Soldier Portable Charger, CE)

- PP-8498/U (Soldier Portable Charger)
- BTC-70819 (Soldier Portable Charger Lite)

Technical Specifications	
National Stock Number	6130-01-630-4260
BT Part Number	BTA-70903
Dimensions	Length: 3.5 in (89 mm) Width: 5.5 in (140 mm) Height: 1.7 in (43 mm)
Weight	0.63 lbs (0.28 kg)
Operating Temperature	-20°C to +50°C (-4°F to +122°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Material/Color	Modified ABS Plastic/Tan
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.



HEADQUARTERS United States 10 Brayton Court, Commack, NY 11725 Phone: 1-631-499-5155 • Fax: 1-631-499-5504

For a complete description of our products refer to Bren-Tronics website at: $\ensuremath{http://www.bren-tronics.com}$

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816 United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.

