

BT-70791A

Rechargeable, Lithium-Ion Battery

TECHNICAL DATASHEET



| Features | | |
|-----------------------------------------------------|------------------------------|--|
| Complies with SMBus v1.1 and | d SBData v1.1 | |
| Only BB-2590/U Qualified for I | Military Use Since 2007 | |
| Total Energy of 207Wh | | |
| Typical Applications | | |
| Robots | | |
| Surveillance / Sensors | | |
| SINCGARS & ASIP (AN/PRC-119) Radios | | |
| FALCON (AN/PRC-150, 117) Radios | | |
| Recommended Charging Platforms | | |
| Charger Part Number | Required Adapter Part Number | |
| BTC-70801 | BTA-70903* or BTA-70834 | |
| BTC-70844 | BTA-70903* or BTA-70834 | |
| BTC-70819, -1, -3 | BTA-70903* or BTA-70834 | |
| BTC-70836 | BTA-70841 or BTA-70820 | |
| BTC-70870, -1, -3 | BTA-70841 or BTA-70820 | |
| BTC-70824-1 | BTA-70782 or BTA-70781 | |
| BTC-70663 | BTA-70782 or BTA-70781A | |
| BTC-70824-2 | (Not Required) | |
| BTC-70791-LR, MR | (Not Required) | |
| BTC-70903-LR, MR1 | (Not Required) | |
| BTC-70822-MR | (Not Required) | |
| BTC-70911-4, -5, -7, -9, 10, -11, -12 | (Not Required) | |
| | | |
| 6140-01-490-4316 | | |
| | | |

| Technical Specifications | |
|---------------------------------|-----------------------------------------------------------------------|
| National Stock Number | 6140-01-490-4316 |
| BT Part Number | BT-70791A |
| Dimensions | Length: 4.4 in (112 mm) Width: 2.4 in (61 mm) Height: 5.0 in (127 mm) |
| Weight | 3.1 lbs (1.4 kg) |
| Nominal Voltage | 28.8V, Two (2) x 14.4V/Section |
| Maximum Voltage | 33.0V, Two (2) x 16.5V/Section |
| | * 33.6V, Two (2) x 16.8V/Section (with the BTA-70903 adapter) |
| Capacity | 6.8Ah in 24V Mode; 13.6Ah in 12V Mode |
| Discharge | 10A Max Continuous / Section |
| Pulse Discharge | 18A (5 sec ON/25 sec OFF) / Section |
| Operating Temperature | –20°C to +60°C (-4°F to +140°F) |
| Recommended Storage Temperature | –40°C to +40°C (-40°F to +104°F) |
| Connector | Floating Type per U.S. Army DWG# SC-C-179495 |
| State of Charge Indicator | 2 Separate 5 Segment LCDs with Constant Display |
| Disposal | Check local regulations (Contains 0% Mercury or Cadmium) |
| | |

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.



HEADQUARTERS United States

For a complete description of our products refer to Bren-Tronics website at: http://www.bren-tronics.com

10 Brayton Court, Commack, NY 11725 Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816 United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.