

BTA-70762-2

Power/SMBus Cable, Right

Features

- The BTA-70762-2 is used to mate with both SMBus contacts and the main connector for:
 - BB-2590/U (BT-70791A, BT-70791E, BT-70791Bx, BT-70791Cx)
 - BB-2557/U (BT-70757, BT-70757A, BT-70757Bx)



Power/SMBus cable shown with BB-2590/U battery (not included)

Related Products

- BTA-70762-1 (x90 SMBus Connector)
- BTA-70762-3 (x90 SMBus Connector w/ Molex Connector, Right)
- BTA-70762-4 (x90 SMBus Connector, Shielded)
- BTA-70762-5 (x90 12V or 24V Discharge Connector)
- BTA-70762-6 (x90 12V Discharge Connector)
- BTK-390/2590 (Unassembled x90 Connector)
- BTK-70762 (Unassembled x90 SMBus Connector)

Technical Specifications

National Stock Number	N/A
BT Part Number	BTA-70762-2
Dimensions	Length: 36.15 in (918.2 mm) Width: 2.35 in (59.7 mm) Height: 1.43 in (36.3 mm)
Weight	0.37 lbs (0.17 kg)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Material/Color	ABS / Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: <http://www.bren-tronics.com>



HEADQUARTERS
United States
10 Brayton Court, Commack, NY 11725
Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816
United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.