

BT-70791CK



Rechargeable, Lithium-Ion Battery

Features

- Complies with SMBus v1.1 and SBData v1.1
- UN/DOT 38.3 Rating: 251Wh
- Comparable to: BB-2590/U, BT-70791Bx, BT-70791Cx and BT-70791Jx
- Certified by US Army to MIL-PRF-32052/1
- Visit: www.bren-tronics.com/patents for patent information
- CE and UKCA Compliant

Typical Applications

Robots

- Surveillance / Sensors
- SINCGARS & ASIP (AN/PRC-119) Radios
- FALCON (AN/PRC-150, 117) Radios

- FP		
	Recommended Charging Platforms	
Loso,	Charger Part Number	Required Adapter Part Number
-	BTC-70801	BTA-70903* or BTA-70834
	BTC-70844	BTA-70903* or BTA-70834
	BTC-70819, -1, -3	BTA-70903* or BTA-70834
	BTC-70836	BTA-70841 or BTA-70820
	BTC-70870, -1, -3	BTA-70841 or BTA-70820
	BTC-70824-1	BTA-70782 or BTA-70781
	BTC-70663	BTA-70782 or BTA-70781A
	BTC-70824-2	(Not Required)
	BTC-70791-LR, MR	(Not Required)
(E CK	BTC-70903-LR, MR1	(Not Required)
	BTK-70822-MR-x Series	(Not Required)
	BTC-70911-xx Series	(Not Required)

Technical Specifications	
National Stock Number	6140-01-490-4316
BT Part Number	BT-70791CK
Dimensions	Length: 4.4 in (112 mm) Width: 2.4 in (61 mm) Height: 5.0 in (127 mm)
Weight	3.1 lbs (1.4 kg)
Nominal Voltage	28.8V, Two (2) x 14.4V/Section
Maximum Voltage	33.6V, Two (2) x 16.8V/Section (supported chargers marked with *)
Capacity	7.5Ah in 24V Mode; 15.0Ah in 12V Mode
Discharge	10A Max Continuous / Section
Pulse Discharge	18A (5 sec ON/25 sec OFF) / Section
Operating Temperature	–20°C to +60°C (-4°F to +140°F)
Recommended Storage Temperature	–40°C to +40°C (-40°F to +104°F)
Connector	6 Pin Floating Type per U.S. Army DWG# SC-C-179495
State of Charge Indicator	2 Separate 5 Segment LCDs with Constant Display
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)
Bren-Tronics is an advanced designer and manufacturer of primary	

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.



United States 10 Brayton Court, Commack, NY 11725 Phone: 1-631-499-5155 • Fax: 1-631-499-5504

For a complete description of our products refer to Bren-Tronics website at: http://www.bren-tronics.com

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816 United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.

