

BTF-70791-P2

DISCHARGER, BB-2590, PROGRAMMABLE SOC

Features

- BTF-70791-P2 can be used in place of large, desktop battery dischargers
- Communicates with the battery through SMBus v1.1 interface
- Microcontroller based operation
- Discharge level can be set by the operator with 4% increments using DIP switches
- Discharges fully charged BB-2590/U (BT-70791xx) to 30% level in less than 6 hours
- The tri-color LED indicator shows the discharge status
- Turns off automatically when the desired discharge level is reached



Related Products

BT-70791xx Series Batteries

BT-70757xx Series Batteries

Technical Specifications

National Stock Number	Pending
BT Part Number	BTF-70791-P2
Dimensions	Length: 4.6 in (117 mm) Width: 2.6 in (67 mm) Height: 2.5 in (63 mm)
Weight	0.9 lb (0.4 kg)
Operating Temperature	0°C to +50°C (32°F to +122°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Material/Color	ABS Tan/Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: <http://www.bren-tronics.com>



HEADQUARTERS

United States

10 Brayton Court, Commack, NY 11725

Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816

United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.