

TECHNICAL DATASHEET

BTK-70838-C

CONNECTOR, CABLE, IdZ



Features

 Unassembled mating connector for use with the Soldier Modernization 				
Program (SMP) batteries				

^ -			HI-L		1 A I	41.
L.C	m	o ta ii	ш	е	vv	ITN
Co	ш	-	110	•	ш	

BT-70838-1/3Cx Battery, Li ION, 1/3SMP II BT-70838-2/3Cx Battery, Li ION, 2/3SMP II BT-70838Cx Battery, Li ION, FULL SPM II



Technical Specifications		
National Stock Number	Pending	
BT Part Number	BTK-70838-C	
Dimensions	Length: 3.0 in (77 mm) Width: 0.9 in (23 mm) Height: 1.1 in (28 mm)	
Weight	0.09 lb (.04 kg)	
Operating Temperature	-20°C to +50°C (-4°F to +122°F)	
Storage Temperature	-40°C to +70°C (-40°F to +158°F)	
Material/Color	Plastic/Black	
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)	

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: http://www.bren-tronics.com



HEADQUARTERS

United States

10 Brayton Court, Commack, NY 11725 Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816

United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.