

# PP-8496/U



# <section-header>

When Ordering Specify P/N: **BTF-70815** 

## SDD1 Battery Discharge Device

### **Product Note:**

The BTF-70815 can be used in place of large, desktop battery dischargers and analyzers to get an accurate remaining capacity and overall health of a battery.

### **Description:**

The BTF-70815 is a battery discharger and analyzer used to determine the State of Health of a BB-390B/U (BT-70790) or BB-2590/U (BT-70791A or BT-70791E).

The LED indicator communicates the results of battery testing, providing an accurate result of battery capability.

### **Technical Data** National Stock Number 6130-01-494-4133 BTF-70815 BT Part No. Length: 4.9 in (116 mm) Width: 2.6 in (67 mm) Height: 2.5 in (64 mm) Dimensions 0.42 Lbs (0.19 Kg) Weight **Operating Temperature** 0°C to +50°C (+32°F to +122°F) Storage Temperature -40°C to +70°C (-40°F to +158°F) Material / Color ABS / Tan BB-2590/U (BT-70791A or BT-70791E) : 10 hours (typical) **Discharge Time** BB-390B/U (BT-70790) : 7.2 hours (typical) For a complete description of our products refer to Bren-Tronics website at: http://www.bren-tronics.com

10 Brayton Court, Commack, NY 11725 Tel 631.499.5155 Fax 631.499.5504 Email sales@bren-tronics.com www.bren-tronics.com