

BT-70676BE

Rechargeable, Lithium-Ion Battery



Features

- Communicates using a Single Wire DQ interface (on side)
- UN/DOT 38.3 Rating: 31 Wh
- Comparable to: BT-70581, BT-70581A, BT-70581B, BT-70581Cx, BT-70676Bx, BB-2001A/U, BA-5301A/U, BT-70720, BT-70720A, MAI-901017, MAI-901018, MAI-901020, and 4866112-004
- Enhanced cold temperature performance
- Absolute state of charge indicator
- Immersion: Tested to 10 meters for 5 minutes, 1 meter for 12 hours

Typical Applications

- AN/PRQ-7 CSEL (Boeing Combat Survivor Evader Locator Radio)

Recommended Charging Platforms

Charger Part Number	Required Adapter Part Number
BTC-70801	BTA-70581A
BTC-70844	BTA-70581A
BTC-70819, -1, -3	BTA-70581A
BTC-70836	BTA-70827
BTC-70870, -1, -3	BTA-70827
BTC-70581-1	(Not Required)

Technical Specifications

National Stock Number	Pending
BT Part Number	BT-70676BE
Dimensions	Length: 3.05 +/- 0.01 in (76.45 +/- 0.25 mm) Width: 1.74 +/- 0.01 in (44.20 +/- 0.25 mm) Height: 2.16 +/- 0.01 in (54.86 +/- 0.25 mm)
Weight	0.51 Lbs (0.23 Kg)
Nominal Voltage	10.8 V
Maximum Voltage	12.6 V
Capacity	2.8 Ah
Discharge	3A Max Continuous
Pulse Discharge	N/A
Operating Temperature	-32°C to +60°C (-25.6°F to +140°F)
Recommended Storage Temperature	-40°C to +40°C (-40°F to +104°F)
Connector	Flat Contacts (side), Fly Wheel Connection (top)
State of Charge Indicator	5 Segment LCD with Constant Display
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: <http://www.bren-tronics.com>



HEADQUARTERS

United States

10 Brayton Court, Commack, NY 11725
Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816

United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice.