



**BB-326/U**

**Rechargeable, Nickel Metal Hydride Battery**



**Features**

- Provides greater capacity over the BB-516/U battery.
- Total Energy: 7.2 Wh

**Typical Applications**

- Laser Range Finder (AN/GVS-5)
- MELIOS (AN/PVS-6)

**Replaces**

Battery Part Number
BB-516/U
BT-70395

**Recommended Charging Platforms**

Charger Part Number	Required Adapter Part Number
BTC-70801	BTA-70395
BTC-70844	BTA-70395
BTC-70819, -1, -3	BTA-70395
BTC-70836	BTA-70841
BTC-70870, -1, -3	BTA-70841

**Technical Specifications**

National Stock Number	6140-01-533-7674
BT Part Number	BT-70787
Dimensions	<b>Length:</b> 1.4 in (36 mm) <b>Width:</b> 1.4 in (36 mm) <b>Height:</b> 3.6 in (91 mm)
Weight	0.59 Lbs (0.27 Kg)
Voltage (Nominal)	24.0 V
Voltage (Maximum)	32.8 V
Capacity	0.3 Ah
Discharge	0.8 A Max Continuous
Pulse Discharge	1.6 A (5 sec ON/25 sec OFF)
Operating Temperature	-20°C to +55°C (-4°F to +131°F)
Storage Temperature	-40°C to +40°C (-40°F to +104°F)
Connector	Flat Nickel Contacts
Absolute State of Charge Display	5 Segment LCD with Constant Display
Disposal	Environmentally Safe – Contains Zero (0)% Mercury or Cadmium

For a complete description of our products refer to Bren-Tronics website at:  
<http://www.bren-tronics.com>



**United States**

10 Brayton Court  
Commack, NY 11725-3197  
Phone: 1-631-499-5155  
Fax: 1-631-499-5504

**Europe**

20 rue Henri Regnault 75014,  
Paris, France  
Phone: +33(0)1-40-59-8051  
Fax: +33(0)1-45-41-5816

**United Kingdom**

Brunel House, Volunteer Way  
Faringdon, Oxfordshire SN7 7YR  
United Kingdom  
Phone: +44-1367-246027  
Fax: +44-1367-246041