

**BT-70791CE**

**Low Temp**

**Rechargeable, Lithium-Ion Battery**

**Features**

- Complies with SMBus v1.1 and SBData v1.1
- UN/DOT 38.3 Rating: 251Wh
- Comparable to: BB-2590/U, BT-70791E, BT-70791Bx and BT-70791Cx
- Absolute state of charge indicator
- Designed, manufactured, and tested to MIL-PRF-32052/1 in the USA
- Protected by one or more U.S. Patents. Please visit for details:  
[www.bren-tronics.com/patents](http://www.bren-tronics.com/patents)
- CB Test Certificate for compliance with battery safety standard IEC 62133
- CE Compliant

**Typical Applications**

- Robots
- Surveillance / Sensors
- SINCGARS & ASIP (AN/PRC-119) Radios
- FALCON (AN/PRC-150, 117) Radios

**Recommended Charging Platforms**

Charger Part Number	Required Adapter Part Number
BTC-70801	BTA-70834 or BTA-70903*
BTC-70844	BTA-70834 or BTA-70903*
BTC-70819, -1, -3	BTA-70834 or BTA-70903*
BTC-70836	BTA-70841 or BTA-70820
BTC-70870, -1, -3	BTA-70841 or BTA-70820
BTC-70824-1	BTA-70782 or BTA-70781
BTC-70663	BTA-70782 or BTA-70781A
BTC-70824-2	(Not Required)
BTC-70791-LR, MR	(Not Required)
BTC-70903-LR*, MR1*	(Not Required)
BTK-70822-MR-x Series	(Not Required)
BTC-70911-xx Series	(Not Required)



**Technical Specifications**

National Stock Number	Pending	Conforms to NSN: 6140-01-490-4316
BT Part Number	BT-70791CE	
Dimensions	<b>Length:</b> 4.4 in (112 mm) <b>Width:</b> 2.4 in (61 mm) <b>Height:</b> 5.0 in (127 mm)	
Weight	3.1 lbs (1.4 kg)	
Nominal Voltage	28.8V, Two (2) x 14.4V/Section	
Maximum Voltage	33.0V, Two (2) x 16.5V/Section	
Capacity	8.7Ah in 24V Mode; 17.4Ah in 12V Mode	
Discharge	10A Max Continuous / Section	
Pulse Discharge	18A (5 sec ON/25 sec OFF) / Section	
Operating Temperature	-30°C to +60°C (-22°F to +140°F)	
Recommended Storage Temperature	-40°C to +40°C (-40°F to +104°F)	
Connector	6 Pin Floating Type per U.S. Army DWG# SC-C-179495	
State of Charge Indicator	2 Separate 5 Segment LCDs with Constant Display	
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)	

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: <http://www.bren-tronics.com>



**HEADQUARTERS**

**United States**

10 Brayton Court, Commack, NY 11725

Phone: 1-631-499-5155 • Fax: 1-631-499-5504

**Europe** • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816

**United Kingdom** • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.