



TECHNICAL DATASHEET

BTA-70912S

Solar Adapter for MR-2791



Features

- Solar Adapter for charging MR-2791 batteries.
- The BTA-70912S when used in conjunction with the appropriate battery charger will charge:
 - MR-2791 (BT-70912AK) in 3.5 hours

Related Products

BTC-70663 (Charger Controller, Li ION (1-4CELL) w/MPPT)

Technical Specifications

National Stock Number	Pending
BT Part Number	BTA-70912S
Dimensions	Length: 3.5 in (89 mm) Width: 1.9 in (49 mm) Height: 1.8 in (46 mm)
Weight	0.66 lbs (0.30 kg)
Operating Temperature	-20°C to +50°C (-4°F to +122°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Material/Color	Modified ABS Plastic/Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: <http://www.bren-tronics.com>



HEADQUARTERS

United States

10 Brayton Court, Commack, NY 11725

Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816

United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.