

TECHNICAL DATASHEET

ALT 170C

Soldier Portable Charger (SPC), CE for ALI-130, 142, 143 and 243



Features

- The BTC-70844-2 is a CE qualified version of the Soldier Portable Charger (SPC).
- It is a state of the art portable battery charger designed for field or depot use.
- The charger is capable of charging up to 8 batteries (2 simultaneously, with 6 batteries in queue) with easy to follow LED lighting sequence.
- For lower capacity batteries the SPC is capable of charging all 8 batteries simultaneously.
- Will charge and maintain a large range of military communication and electronics batteries using a designated adapter.
- Charging Software is upgradeable in the field or a lab environment through the RS 232 port.
- Powered from 20V-33V DC, 15A, 85-264V AC, 47 to 440 Hz, 375 VA.
- Dedicated for the ALI-130, 142, 143, and 243 batteries.
- The ALT 170C includes one BTC-70844 (SPC, CE) and 4 BTA-70589A (SPC Adapter).

Related Products

- BTC-70801 (Soldier Portable Charger)
- BTC-70819 (Soldier Portable Charger Lite)
- BTC-70819-1 (Soldier Portable Charger Lite, EU)
- BTC-70819-3 (Soldier Portable Charger Lite, 12V DC)
- BTA-70835 (24V DC SPC)
- BTA-70844-24 (DC Power Cable w/ Ring Lugs)
- BTA-70844-24AL (DC Power Cable w/ Alligator Clips)
- 590233-3 (AC Input Cable, Euro) included
- 590233-10 (AC Input Cable, US)
- 590233-UK (AC Input Cable, UK)

Technical Specifications

National Stock Number	6130-01-606-9496
BT Part Number	BTC-70844-2
Dimensions	Charger Length: 22.8 in (579 mm) Width: 14.6 in (371 mm) Height: 9.0 in (229 mm)
	Cable Length: 22.0 in (559 mm)
	Battery Adapter Length: 2.7 in (69 mm) Width: 1.9 in (48 mm) Height: 1.7 in (43 mm)
	Connector Length: 2.9 in (75 mm) Width: 1.1 in (28 mm) Height: 2.2 in (56 mm)
Weight	30.3 Lbs (13.8 Kg)
Operating Temperature	-20°C to +50°C (-4°F to +122°F)
Storage Temperature	-40°C to +70°C (-40°F to 158°F)
Material/Color	High impact ABS/Olive Drab
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: <http://www.bren-tronics.com>



HEADQUARTERS

United States

10 Brayton Court, Commack, NY 11725

Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816

United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.