



TECHNICAL DATASHEET

BTP-592212-x

POWER CORD, IEC C7, 6 FT SERIES

Features

- The BTP-592212-x Series of interchangeable power cords are used on the following:
 - BTC-70903-MR1 (Charger, Med-Rate, 2590/390/2557, AC, FC)
 - BTC-70791-MR (Charger, Med-Rate, 2590/390/2557, AC)
 - BTP-591955-1 (AC/DC Converter, w/Trailer Hitch, US)



Related Products

- BTP-592212-AU (Power Cord, IEC C7, 6 Ft, AU)
- BTP-592212-EU (Power Cord, IEC C7, 6 Ft, EU)
- BTP-592212-UK (Power Cord, IEC C7, 6 Ft, UK)

Technical Specifications

National Stock Number	Pending
BT Part Number	BTP-592212-x Series
Dimensions	Length: 6 ft (1,829 mm)
Weight	0.20 lbs (0.09 kg)
Operating Temperature	-20°C to +50°C (-4°F to +122°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Color	Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

Bren-Tronics is an advanced designer and manufacturer of primary and rechargeable batteries, chargers and complete energy storage systems from watt hours to megawatt hours.

For a complete description of our products refer to Bren-Tronics website at: <http://www.bren-tronics.com>



HEADQUARTERS

United States

10 Brayton Court, Commack, NY 11725

Phone: 1-631-499-5155 • Fax: 1-631-499-5504

Europe • 20 rue Henri Regnault 75014, Paris, France • Phone: +33(0)1-40-59-8051 • Fax: +33(0)1-45-41-5816

United Kingdom • 7 Airfield House, Kingston Business Park, Kingston Bagpuize, Oxon OX13 5FD • Phone: +44-1865-822322 • Fax: +44-1865-822301

Data presented in this document is subject to change without notice. This is for marketing and sales purposes only. This is not a controlled document. Please contact Bren-Tronics for latest specifications.